

Variomat Giga GS 3, control module for Variomat Giga DH stations

Article number: 8912600

reflex

Thinking solutions.



Features

Type	GS 3
Control type	Control Touch
For hydraulic module	GH 90, GH 100
Max. permissible system temperature	120 °C
Max. perm. safety temperature	110 °C
Max. perm. operating temperature	90 °C
Pressure/temperature	16 bar 90 °C
Max. perm. operating pressure	16 bar
Type of protection	IP 54
Electric connection	400V/50Hz
Max. electrical rated power	6.00 kW
Height	921 mm
Width	380 mm
Depth	477 mm
Weight	7.10 kg

Description

Variomat Giga Control Unit GS

For control and operation of the Variomat Giga pump controlled pressurisation system. Actuation of the corresponding Variomat Giga GH hydraulics (separate product), assembled and internally wired with the appropriate components so that it is fully functional. Constructed in compliance with DIN EN 12828 and the requirements of VDI 4708, with CE marking. The Control Touch control unit with TFT colour display, including communication electronics, is integrated into a robust plastic housing designed as a panel and mounted horizontally directly on the controller. An optional separate and vertical wall mounting at a maximum distance of three metres from the power electronics is possible. Communication electronics comprising:

- 4.3" resistive colour touch display for programming, operating documentation and monitoring, as well as the provision of help texts for all functions
- two RS485 interfaces as data and communication interfaces
- a serial TTL interface with two connection terminals for connecting 2 I/O circuit boards
- a potential free output for transmitting the group message
- two galvanically isolated analogue outputs, e.g. for system pressure
- an input for analysis of contact water meters

- Slot for an HMS network module, one SD card, e.g. for data read-out, software updates, etc.

The power electronics are installed in a dedicated plastic control cabinet which is mounted directly below the operating unit. Power supply is via a main switch. Featuring in detail:

- Main switch on housing exterior
- Pump control
- Cable management for external connections
- Mounting slot for optional modules

Control unit completely piped and wired ready for connection according to VDE regulations. System connections by means of integrated shut-off valves.

Control Touch is a fully automatic and freely programmable microprocessor control with touchscreen operation, real-time clock, differentiating error and parameter memory, combined graphical and clear-text display of system pressure, tank level and all relevant operating and fault messages, functional diagram, signalling of the active operating mode, collective fault message, low water level, functioning of pump, overflow valve and make-up valve. Functioning of the pressurisation in the limits ± 0.2 bar including pump monitoring. Optimised system water degassing due to patented, fully-automatic overflow control with cycles for continuous, interval and run-on degassing. Controlled make-up, automatic interruption and fault message upon exceeding of the runtime and/or the number of cycles. Processing of the signal of a contact water meter for maximum volume limit and/or capacity evaluation of ion exchangers located in the make-up line. Documentation and control of the entire system in respect of the above mentioned parameters.