

Reflexomat RF 5000, for Reflexomat pressurisation stations, grey, 6 bar

Article number: 8652705



Features

Type	RF 5000
Colour	grey
Nominal volume	5000 l
Max. useful volume	4500 l
Max. permissible system temperature	120 °C
Max. perm. safety temperature	110 °C
Min. perm. operating temperature	-10 °C
Max. perm. operating temperature	70 °C
Max. perm. operating pressure	6 bar
Connection	DN65/PN6
Diameter	1500 mm
Height	3588 mm
High water connection	490 mm
Tilt dimension approx.	3630 mm
Weight	1115.00 kg

Description

Reflexomat RF

Diaphragm expansion vessel for Reflexomat compressor-controlled pressure maintenance station for sealed heating and cooling systems. Approval according to the EU Pressure Equipment Directive 2014/68/EU. Built according to DIN EN 13831 and VDI 4708 or AD 2000.

- Floor-standing with pedestal
- Replaceable butyl bladder according to DIN EN 13831
- Plastic-coated inside and outside
- Vessel protection via component-tested air safety valve (SV)
- Including welded side sleeve for connection of a membrane rupture detector

Note:

No licence requirement according to SWKI HE301-01 and SVTI for (PSV * VN ≤ 3,000 bar * litre).