

Reflexomat Primary vessel RG 500, for Reflexomat pressurisation stations, grey, 6 bar

Article number: 8799400



Features

Type	RG 500
Colour	grey
Nominal volume	500 l
Max. useful volume	450 l
Max. permissible system temperature	120 °C
Max. perm. safety temperature	110 °C
Min. perm. operating temperature	-10 °C
Max. perm. operating temperature	70 °C
Max. perm. operating pressure	6 bar
Connection	G1"
Diameter	740 mm
Height	1497 mm
High water connection	177 mm
Tilt dimension approx.	1510 mm
Weight	78.70 kg

Description

Reflexomat RG

Diaphragm expansion vessel for Reflexomat compressor-controlled pressure maintenance station for sealed heating and cooling systems. Approval according to the EU Pressure Equipment Directive 2014/68/EU. Built according to DIN EN 13831 and VDI 4708 or AD 2000.

- Floor-standing with pedestal
- replaceable butyl bladder according to DIN EN 13831
- , plastic-coated inside and outside
- , vessel protection via component-tested air safety valve (SV)
- including welded side sleeve for connection of a membrane rupture detector
- RG" primary vessel including a transducer for level measurement

Note:

No licence requirement according to SWKI HE301-01 and SVTI for (PSV * VN ≤ 3,000 bar * litre).