

# Variomat secondary vessel VF 400, for Variomat pressurisation units, grey, 6 bar

Article number: 8610200



## Features

|                                     |          |
|-------------------------------------|----------|
| Type                                | VF 400   |
| Colour                              | grey     |
| Nominal volume                      | 400 l    |
| Max. useful volume                  | 360 l    |
| Max. permissible system temperature | 120 °C   |
| Max. perm. safety temperature       | 110 °C   |
| Min. perm. operating temperature    | 0 °C     |
| Max. perm. operating temperature    | 70 °C    |
| Max. perm. operating pressure       | 6 bar    |
| Connection                          | G1"      |
| Diameter                            | 740 mm   |
| Height                              | 1344 mm  |
| High water connection               | 178 mm   |
| Tilt dimension approx.              | 1353 mm  |
| Weight                              | 69.90 kg |

## Description

### Variomat VF

Diaphragm expansion vessel for Variomat one or two-pump controlled pressure maintenance stations, unpressurised, closed to atmosphere. Approval according to the EU Pressure Equipment Directive 2014/68/EU. Built according to DIN EN 13831 and VDI 4708 or AD 2000.

- Floor-standing with foot structure
- Replaceable full diaphragm - compliant with DIN EN 13831
- Exterior plastic-coated
- With dipstick tube degassing
- including welded side socket for connection of a bladder rupture detector
- basic vessels VG incl. transducer for level sensing