# Variomat primary vessel VG 2000, for Variomat pressurisation stations, grey, 6 bar

Article number: 8601005

Thinking solutions.




## Features

| | |
|---|---|
| Type | VG 2000 |
| Colour | grey |
| Nominal volume | 2000 l |
| Max. useful volume | 1800 l |
| Max. permissible system temperature | 120 °C |
| Max. perm. safety temperature | 110 °C |
| Min. perm. operating temperature | -10 °C |
| Max. perm. operating temperature | 70 °C |
| Max. perm. operating pressure | 6 bar |
| Connection | G1" |
| Diameter | 1200 mm |
| Height | 2587 mm |
| High water connection | 460 mm |
| Tilt dimension approx. | 2609 mm |
| Weight | 400.00 kg |

## Description

Variomat VG
Diaphragm expansion vessel for Variomat one or two-pump controlled pressure maintenance stations, unpressurised, closed to atmosphere. Approval according to the EU Pressure Equipment Directive 2014/68/EU. The vessels are manufactured in accordance with DIN EN 13831, VDI 4708 and AD 2000.

- Floor-standing with foot structure
- Replaceable full diaphragm - compliant with DIN EN 13831
- Exterior plastic-coated
- With dipstick tube degassing
- including welded side socket for connection of a bladder rupture detector
- basic vessels VG incl. transducer for level sensing