

Storatherm Aqua AF 1000/1_C, hot water storage tank with foil jacket, white, 10 bar

Article number: 7848100



Thinking solutions.



Features

Type	AF 1000/1_C
Colour	white
Insulation type	foil jacket
Insulation strength	107.5 mm
Energy efficiency class	C
Nominal capacity	932 l
Rated content corrugated pipe	41 l
Built acc. to	EN 12897
Perm. operating temperature heat exchanger	110 °C
Max. perm. operating pressure	10 bar
Perm. operating pressure heat exchanger	16 bar
Operating pressure	10 bar
Anschluss Flansch EFHR (berechnet)	DN180
Drinking water connection	R 1 1/4"
Connection heat surface(s)	R 1 1/4"
Circulation connection	R 3/4"
Connection cold/hot water	R 1 1/4"
Connection flow/return	R 1 1/4"
Conventional NL coefficient	38.8
Heat maintaining losses	142 W
Heating surface top	4.48 m ²
Diameter	1065 mm
Diameter without insulation	850 mm
Height	2058 mm
Height without insul.	1962 mm
Depth	1152 mm
Tilt dimension approx.	2173 mm
Weight	288.10 kg

Description

Storatherm Aqua

Hot water tank for indirect domestic hot water heating in an upright version with an internal heat exchanger.

Storage tank of steel S235JR+AR, designed according to DIN EN 12897 and the Pressure Equipment Directive 2014/68/EU. Enamelling for hygienic perfect drinking water is performed according to DIN 4753 T3.

DHW tank up to 500 litre insulated with non-removable highly efficient insulation system according to DIN 4102-1 material class B2; DHW tank > 500 to 1000 litre insulated with 100mm; DHW tank > 1000 litre with 120mm removable fleece insulation, according to DIN 4102-1 material class B2. Tanks up to 2000 litres are supplied ready-insulated. Tanks greater than 3000 litres are transported horizontally, without insulation. Insulation must be ordered separately.

Drinking water tank up to 500 litres available in energy efficiency classes A, B and C. DHW tank > 500 litres only available in energy efficiency class C.

The heat losses are measured on an externally certified test bed.