

Reflex DD 2, flow through expansion vessel, green, 10/4 bar

Article number: 7381500



Features

| | |
|--------------------------------------|---------|
| Type | DD 2 |
| Colour | green |
| Diaphragm material | butyl |
| Nominal volume | 2 l |
| Max. useful volume | 1.8 l |
| Max. permissible system temperature | 70 °C |
| Min. perm. operating temperature | -10 °C |
| max. perm. operating temperature | 70 °C |
| Max. perm. operating pressure | 10 bar |
| Factory provided gas supply pressure | 4 bar |
| Connection | G 3/4" |
| Diameter | 132 mm |
| Height | 269 mm |
| Tilt dimension approx. | 300 mm |
| Weight | 1.00 kg |

Description

Reflex DD

Flowed through diaphragm expansion tank for DHW systems, water supply installations and pressure-boosting systems. With diaphragm according to the elastomer directive and W 270. Exterior and interior coating in compliance with KTW-A. Only suitable for cold water systems. The flow is implemented using a high-flow circulation star and the enclosed 3/4" T-piece

Vessels are designed and manufactured according to DIN EN 13831. Checked according to DIN 4807 part 5. Vessels with a permissible operating pressure of 10/16 bar with DIN DVGW Reg. no. NW-0411AT2534. approval according to Pressure Equipment Directive 2014/68/EU

- circulation with high-flow circulation star
- parts in contact with water are corrosion-protected
- non-replaceable bladder according to DIN EN 13831 DIN 4807 T5, KTW-C and W270
- interior and exterior coating in compliance with KTW-A
- may be combined with the Flowjet — flow through valve
- 33 litres with brackets
- only for use in cold water pipes (consider installation and operating instructions)