

Storatherm Aqua Solar AF 300/2_A, Solar Storage, white, 10 bar

Article number: 7355700



Features

Type	AF 300/2_A
Colour	white
Insulation type	foil jacket
Insulation strength	76.5 mm
Energy efficiency class	A
Nominal Capacity of potable water storage tank	288 l
Rated content corrugated pipe	6 l
Built acc. to	EN 12897
Operating Temperature of potable water storage tank	95 °C
Perm. operating temperature heat exchanger	110 °C
Operating Overpressure of potable water storage tank	10 bar
Perm. operating pressure heat exchanger	16 bar
EFHR flange connection	DN110
EEHR sleeve connection	G 1 1/2"
Drinking water connection	R 1"
Connection heat surface(s)	R 1"
Circulation connection	R 3/4"
Connection cold/hot water	R 1"
Connection flow/return	R 1"
Conventional NL coefficient	2.2
Solar NL coefficient	8.4
Heat retention losses potable water storage tank	48 W
Heating surface top	0.82 m²
Heating surface bottom	1.42 m²
Diameter without insulation	597 mm
Height	1364 mm
Height without insul.	1266 mm
Width	750 mm
Depth	844 mm
Tilt dimension approx.	1572 mm
Weight	100.00 kg

Description

Storatherm Aqua Solar

Hot water tank for indirect domestic hot water heating with solar support in an upright version with two internal heat exchangers.

Storage tank of steel S235JR+AR, designed according to DIN EN 12897 and the Pressure Equipment Directive 2014/68/EU. Enamelling for hygienic perfect drinking water is performed according to DIN 4753 T3.

DHW tank up to 500 litre insulated with non-removable highly efficient insulation system according to DIN 4102-1 material class B2; DHW tank > 500 to 1000 litre insulated with 100mm; DHW tank > 1000 litre with 120mm removable fleece insulation, according to DIN 4102-1 material class B2. Tanks up to 2000 litres are supplied ready-insulated. Tanks greater than 3000 litres are transported horizontally, without insulation. Insulation must be ordered separately.

Drinking water tank up to 500 litres available in energy efficiency classes A, B and C. DHW tank > 500 litres only available in energy efficiency class C.

The heat losses are measured on an externally certified test bed.