

# Reflex Storatherm Aqua Compact AC 60/1E-W\_B, wall-mounted tank with steel sheet jacket, PUR foam, white, 10 bar

**reflex**

Thinking solutions.



## Features

Type	AC 60/1E-W_B
Colour	white
Insulation	✓
Insulation type	steel sheet jacket, PUR foam
Insulation strength	30 mm
Energy efficiency class	B
Nominal capacity	65 l
Built acc. to	EN 12897
Operating temperature	95 °C
Perm. operating temperature heat exchanger	110 °C
Perm. operating pressure heat exchanger	10 bar
Operating pressure	10 bar
Electric connection	230V/50Hz, 400V/50Hz
Drinking water connection	R 3/4"
Connection heat surface(s)	R 3/4"
Connection cold/hot water	R 3/4"
Connection flow/return	R 3/4"
NL coefficient top	1.0
Heat maintaining losses	38 W
Max. electrical rated power	3.00 kW
Heating surface top	0.75 m²
Height	747 mm
Width	461 mm
Depth	461 mm
Weight	58.00 kg

## Description

### Reflex Storatherm Aqua Compact

Hot water tank for indirect domestic hot water heating in wall-mounted version optionally with an internal heat exchanger, immersion heater or a combination of the two.

Storage tank of steel S235JR+AR, designed according to DIN EN 12897 and the Pressure Equipment Directive 2014/68/EU. Enamelling for hygienic perfect drinking water is performed according to DIN 4753 T3.

DHW tank up to 500 litre insulated with non-removable highly efficient insulation system according to DIN 4102-1 material class B2; DHW tank > 500 to 1000 litre insulated with 100mm; DHW tank > 1000 litre with 120mm removable fleece insulation, according to DIN 4102-1 material class B2.

Drinking water tank up to 500 litres available in energy efficiency classes B and C. DHW tank > 500 litres only available in energy efficiency class C.

The heat losses are measured on an externally certified test bed.

