

# SINUS ProfiFixx MK65 P40 regulated flanged pump group DN65, for pump DN40, 220 mm, 3-way mixer 230V

**reflex**

Thinking solutions.



## Features

Type	MK65 P40
Pump group dimension	DN65
Pump dimension	DN40
Installed length installer supplied pump	220 mm
Type three-way mixer	ESBE VRG131 50-40 Rp2"
Flow capacity of the three-way mixer	40.0
Actuator type	ESBE ARA661 3-point SPDT 230 V
Operating temperature	-10 °C - 110 °C
Operating pressure	0 bar - 6 bar

## Description

Flange pump group comprising pre-assembled and pre-insulated heating circuits compliant with the current building regulations (GEG) for direct installation without any on-site welding. Implemented with a regulated design with a three-way mixer. The entire ProfiFixx system is insulated in a visually uniform manner. The insulation is fitted using the supplied stainless-steel straps including quick-release connections and can be opened and closed again for maintenance purposes. The site provided pump is also freely accessible during operation, without it being necessary to remove the insulation.

The pump groups are provided with upper threaded flanges (female thread) for system-side connection. One ½" sensor sleeve each in flow and return. The insulation is not diffusion-tight.

The component is checked for 100% leak-tightness and primed in the factory.

