Reflex G 3000, upright diaphragm expansion vessel, grey, 6/2 bar

Article number: 8544605

Thinking solutions.



Features

Type	G 3000
Colour	grey
Diaphragm material	butyl
Nominal volume	3000 l
Max. useful volume	2700 l
Max. permissible system temperature	120 °C
Min. perm. operating temperature	-10 °C
Max. perm. operating temperature	70 °C
Max. perm. operating pressure	6 bar
Factory provided gas supply pressure	2 bar
Connection	DN65/PN6
Diameter	1500 mm
Height	2490 mm
High water connection	334 mm
Tilt dimension approx.	2595 mm
Weight	620.00 kg

Description

Reflex G
Diaphragm expansion tank for sealed heating and cold water systems. The vessels are manufactured in accordance with DIN EN 13831, VDI 4708 and AD 2000. Approval according to Pressure Equipment Directive 2014/68/EC.

- durable epoxy resin coating
- replaceable bladder according to DIN EN 13831
- for antifreeze additive of at least 25 – 50 %
- pressure gauge and supply pressure valve protected by clip
- upright configuration
- max. permissible system temperature 120°C
- max. permissible operating temperature 70°C
- connections:
  → up to 1,000 l / Ø 740 mm with threaded connections
  → from 1,000 l / Ø 1,000 mm with flange connections DN65/PN6 or DN65/PN16
- sleeve for optional membrane rupture detector
- with inspection opening (from 1,000 litres with Ø 1,000 mm)