

# Reflexomat RF 300, for Reflexomat pressurisation stations, grey, 6 bar

Article number: 8789200



## Features

|                                     |          |
|-------------------------------------|----------|
| Type                                | RF 300   |
| Colour                              | grey     |
| Nominal volume                      | 300 l    |
| Max. useful volume                  | 270 l    |
| Max. permissible system temperature | 120 °C   |
| Max. perm. safety temperature       | 110 °C   |
| Min. perm. operating temperature    | -10 °C   |
| Max. perm. operating temperature    | 70 °C    |
| Max. perm. operating pressure       | 6 bar    |
| Connection                          | G1"      |
| Diameter                            | 634 mm   |
| Height                              | 1267 mm  |
| High water connection               | 191 mm   |
| Tilt dimension approx.              | 1276 mm  |
| Weight                              | 60.50 kg |

## Description

### Reflexomat RF

Diaphragm expansion vessel for Reflexomat compressor-controlled pressure maintenance station for sealed heating and cooling systems. Approval according to the EU Pressure Equipment Directive 2014/68/EU. Built according to DIN EN 13831 and VDI 4708 or AD 2000.

- Floor-standing with pedestal
- Replaceable butyl bladder according to DIN EN 13831
- Plastic-coated inside and outside
- Vessel protection via component-tested air safety valve (SV)
- Including welded side sleeve for connection of a membrane rupture detector

### Note:

No licence requirement according to SWKI HE301-01 and SVTI for (PSV \* VN ≤ 3,000 bar \* litre).