Variomat primary vessel VG 800, for Variomat pressurisation stations, grey, 6 bar

Article number: 8600511

reflex
Thinking solutions.



Features

Type	VG 800
Colour	grey
Nominal volume	800 l
Max. useful volume	720 l
Max. permissible system temperature	120 °C
Max. perm. safety temperature	110 °C
Min. perm. operating temperature	-10 °C
Max. perm. operating temperature	70 °C
Max. perm. operating pressure	6 bar
Connection	G1"
Diameter	740 mm
Height	2272 mm
High water connection	177 mm
Tilt dimension approx.	2277 mm
Weight	109.90 kg

Description

Variomat VG
Diaphragm expansion vessel for Variomat one or two-pump controlled pressure maintenance stations, unpressurised, closed to atmosphere. Approval according to the EU Pressure Equipment Directive 2014/68/EU. The vessels are manufactured in accordance with DIN EN 13831, VDI 4708 and AD 2000.

- Floor-standing with foot structure
- Replaceable full diaphragm - compliant with DIN EN 13831
- Exterior plastic-coated
- With dipstick tube degassing
- including welded side socket for connection of a bladder rupture detector
- basic vessels VG incl. transducer for level sensing

Reflex Winkelmann GmbH • Gersteinstrasse 19 • 59227 Ahlen, Germany
+49 2382 7069-0 • www.reflex-winkelmann.com • info@reflex.de