

Storatherm Aqua Heat Pump AH 150/1_B, high efficiency tank with foil jacket, white, 10 bar

Article number: 7864600



Features

Type	AH 150/1_B
Colour	white
Insulation type	foil jacket
Insulation strength	75 mm
Energy efficiency class	B
Nominal capacity	144 l
Rated content corrugated pipe	11 l
Built acc. to	EN 12897
Operating temperature	95 °C
Perm. operating temperature heat exchanger	110 °C
Max. perm. operating pressure	10 bar
Perm. operating pressure heat exchanger	10 bar
Operating pressure	10 bar
Anschluss Flansch EFHR (berechnet)	DN110
Drinking water connection	R 3/4"
Connection heat surface(s)	G1"
Circulation connection	R 3/4"
Connection cold/hot water	R 3/4"
Connection flow/return	G1"
Conventional NL coefficient	5,3
Heat maintaining losses	41 W
V40 (EN12897)	274 L
Heating surface top	1,59 m²
Diameter	600 mm
Diameter without insulation	450 mm
Height	1172 mm
Height without insul.	1146 mm
Tilt dimension approx.	1285 mm
Weight	57.00 kg

Description

Storatherm Aqua Heat Pump

Hot water tank for indirect domestic hot water heating especially for heat pump applications in an upright version with one or two internal heat exchangers.

Storage tank of steel S235JR+AR, designed according to DIN EN 12897 and the Pressure Equipment Directive 2014/68/EU. Enamelling for hygienic perfect drinking water is performed according to DIN 4753 T3.

DHW tank up to 500 litre insulated with non-removable highly efficient insulation system according to DIN 4102-1 material class B2; DHW tank > 500 to 1000 litre insulated with 100mm; DHW tank > 1000 litre with 120mm removable fleece insulation, according to DIN 4102-1 material class B2.

Drinking water tank up to 500 litres available in energy efficiency classes B and C. DHW tank > 500 litres only available in energy efficiency class C.

The heat losses are measured on an externally certified test bed.