

Storatherm Heat Mini V 100, Buffer cylinder for heating systems, grey, 4 bar

Article number: 7352450



Features

Type	V 100
Colour	grey
Insulation type	EPP
Insulation strength	35 mm
Energy efficiency class	B
Nominal capacity	106 l
Number of sleeves	2 St.
Operating temperature	15 – 95 °C
Max. perm. operating pressure	4 bar
Operating pressure	4 bar
Connection sleeve/flange	G 1 1/2"
Heat maintaining losses	49 W
Diameter	580 mm
Diameter without insulation	480 mm
Height	893 mm
Height without insul.	738 mm
Depth	563 mm
Tilt dimension approx.	1032 mm
Weight	22.10 kg

Description

Storatherm Heat Mini V 100

Buffer tank for storing heating water. Without flange, without internal heat exchangers. The two connection nozzles arranged as charging or discharging nozzles, of threaded 1 1/2 inch design, respectively arranged at the top and bottom – are vertically aligned.

Storage container of steel DC04, inside uncoated and outside painted. Buffer tank, insulated with 35mm removable EPP insulation, according to DIN 4102-1 material class B2.

Energy efficiency class B according to DIN EN 12897:2020-05. The heat losses are measured on a certified test bed.

Available in 25, 50, 75 and 100l volumes.

25l and 50l hot water storage tanks are wall-mounted.

75l and 100l hot water storage tanks are floor-standing.