

# Storatherm Aqua Heat Pump AH 750/1\_C, high efficiency tank with foil jacket, white, 10 bar

Article number: 7845800



Thinking solutions.



## Features

Type	AH 750/1_C
Colour	white
Insulation type	foil jacket
Insulation strength	105 mm
Energy efficiency class	C
Nominal capacity	694 l
Rated content corrugated pipe	49 l
Built acc. to	EN 12897
Perm. operating temperature heat exchanger	110 °C
Max. perm. operating pressure	10 bar
Perm. operating pressure heat exchanger	10 bar
Operating pressure	10 bar
Anschluss Flansch EFHR (berechnet)	DN180
EEHR sleeve connection	G 1 1/2"
Drinking water connection	R 1 1/4"
Connection heat surface(s)	R 1 1/4"
Circulation connection	R 3/4"
Connection cold/hot water	R 1 1/4"
Connection flow/return	R 1 1/4"
Conventional NL coefficient	40.0
Heat maintaining losses	141 W
Heating surface top	7.06 m <sup>2</sup>
Diameter	960 mm
Diameter without insulation	750 mm
Height	2052 mm
Height without insul.	1930 mm
Depth	1047 mm
Tilt dimension approx.	2119 mm
Weight	263.00 kg

## Description

### Storatherm Aqua Heat Pump

Hot water tank for indirect domestic hot water heating especially for heat pump applications in an upright version with one or two internal heat exchangers.

Storage tank of steel S235JR+AR, designed according to DIN EN 12897 and the Pressure Equipment Directive 2014/68/EU. Enamelling for hygienic perfect drinking water is performed according to DIN 4753 T3.

DHW tank up to 500 litre insulated with non-removable highly efficient insulation system according to DIN 4102-1 material class B2; DHW tank > 500 to 1000 litre insulated with 100mm; DHW tank > 1000 litre with 120mm removable fleece insulation, according to DIN 4102-1 material class B2.

Drinking water tank up to 500 litres available in energy efficiency classes B and C. DHW tank > 500 litres only available in energy efficiency class C.

The heat losses are measured on an externally certified test bed.