

Storatherm Aqua AF 300/1M_B, hot water storage tank with foil jacket, PUR foam, silver, 10 bar

Article number: 7861300



Thinking solutions.



Features

Type	AF 300/1M_B
Colour	silver
Insulation type	foil jacket, PUR foam
Insulation strength	51.5 mm
Energy efficiency class	B
Nominal capacity	303 l
Rated content corrugated pipe	10 l
Built acc. to	EN 12897
Perm. operating temperature heat exchanger	110 °C
Max. perm. operating pressure	10 bar
Perm. operating pressure heat exchanger	16 bar
Operating pressure	10 bar
Drinking water connection	R 1"
Connection heat surface(s)	R 1"
Connection cold/hot water	R 1"
Connection flow/return	R 1"
Conventional NL coefficient	11.1
Heat maintaining losses	70 W
Heating surface top	1.40 m ²
Diameter	700 mm
Height	1334 mm
Tilt dimension approx.	1441 mm
Weight	82.80 kg

Description

Storatherm Aqua

Hot water tank for indirect domestic hot water heating in an upright version with an internal heat exchanger.

Storage tank of steel S235JR+AR, designed according to DIN EN 12897 and the Pressure Equipment Directive 2014/68/EU. Enamelling for hygienic perfect drinking water is performed according to DIN 4753 T3.

DHW tank up to 500 litre insulated with non-removable highly efficient insulation system according to DIN 4102-1 material class B2; DHW tank > 500 to 1000 litre insulated with 100mm; DHW tank > 1000 litre with 120mm removable fleece insulation, according to DIN 4102-1 material class B2. Tanks up to 2000 litres are supplied ready-insulated. Tanks greater than 3000 litres are transported horizontally, without insulation. Insulation must be ordered separately.

Drinking water tank up to 500 litres available in energy efficiency classes A, B and C. DHW tank > 500 litres only available in energy efficiency class C.

The heat losses are measured on an externally certified test bed.