# Variomat Giga secondary vessel GF 1500, for Variomat Giga pressurisation stations, grey, 6 bar

Article number: 8930305

Thinking solutions.




## Features

| | |
|---|---|
| Type | GF 1500 |
| Colour | grey |
| Nominal volume | 1500 l |
| Max. useful volume | 1350 l |
| Max. permissible system temperature | 120 °C |
| Max. perm. safety temperature | 110 °C |
| Min. perm. operating temperature | -10 °C |
| Max. perm. operating temperature | 70 °C |
| Max. perm. operating pressure | 6 bar |
| Connection | DN65/PN6 |
| Diameter | 1200 mm |
| Height | 2158 mm |
| High water connection | 195 mm |
| Tilt dimension approx. | 2153 mm |
| Weight | 340.00 kg |

## Description

Variomat Giga GF
Diaphragm expansion vessel for Variomat Giga pressure maintenance stations, unpressurised, closed to atmosphere. Approval according to the EU Pressure Equipment Directive 2014/68/EU. The vessels are manufactured in accordance with DIN EN 13831, VDI 4708 and AD 2000.

- Floor-standing with foot structure
- Replaceable full diaphragm - compliant with DIN EN 13831
- Exterior plastic-coated
- With dipstick tube degassing
- secondary vessels GF without transducer for level sensing


Reflex Winkelmann GmbH • Gersteinstrasse 19 • 59227 Ahlen, Germany
+49 2382 7069-0 • www.reflex-winkelmann.com • info@reflex.de