

Extwin TW 22 V, Micro-bubble/dirt separator with clamping ring of brass, 110 °C, 10 bar

Article number: 9253500



Features

Type	TW 22 V
Housing material	brass
Magnet type	without magnet
Installation variant	vertical
Operating temperature	0 °C - 110 °C
Operating pressure	10 bar
Connection	22 mm
Cleaning connection	G 3/4"
Connection variant	clamping ring
Max. volume flow	1.2 m³/h
Flow rate characteristic value kvs	10.7 m³/h
Diameter	65 mm
Height	266 mm
Width	175 mm
Installation length	98 mm
Weight	2.10 kg

Description

Extwin

Combined air/microbubble and sludge separator for heating and cold water systems or sealed liquid-filled system circuits.

Suitable for the media water and water/glycol mixtures up to a mixing ratio of 50/50%.

Fitting for collecting gas bubbles from the liquid flow via optimised separating element or automatic, permanent discharge into the atmosphere via integrated, able to be isolated, Exvoid T large ventilator with 3-way valve bottom part.

Fitting for removing particles with a size from 5.0 micrometres from the flow of liquid by use of an insert designed specially for the purpose.

The cleaning and emptying of the dirt collection chamber is possible via a dedicated desludging ball valve without any necessity to interrupt operation.

Optional retro-fitting with an Exferro magnet insert for separation of ferromagnetic particles from the fluid flow.