


Storatherm Heat HF 800/R2_C, Buffer cylinder for heating and cooling systems, grey, 10 bar

Article number: 7353600



Features

Type	HF 800/R2_C
Colour	grey
Insulation	✓
Insulation type	foil jacket
Insulation strength	100 mm
Energy efficiency class	C
Nominal capacity	777 l
Number of sleeves	4 St.
Operating temperature	95 °C
Max. perm. operating pressure	10 bar
Operating pressure	10 bar
Connection	DN80/PN16
Heat maintaining losses	132 W
Diameter	990 mm
Height	1892 mm
Tilt dimension approx.	1938 mm
Weight	197.00 kg

Description

Storatherm Heat

Buffer tank for storing heating and cooling water.

The series of connectors (DIN EN 1092-1) for heat generators and consumers are arranged opposite to each other as charging or discharging connectors. Between these series of connectors there also vertically arranged screw-in options for sensor sleeves, thermometers or similar (3 x Rp 1 1/2, 1 x Rp 1). In addition, there are two DN 180 flange connections.

Storage tank of steel S235JR+AR, inside uncoated and outside corrosion protected.

Buffer tank up to 1000 litre insulated with 100mm, buffer tank > 1000 litre with 120mm removable fleece insulation; according to DIN 4102-1 material class B2. Tank available in energy efficiency class C.

The heat losses are measured on an externally certified test bed.