

Fillsoft housing FG II, Basic valve for makeup water treatment

Article number: 9125661



Features

Type	FG II
Cartridge places	2 pc(s).
Max. perm. operating temperature	40 °C
Storage temperature	-
Max. perm. operating pressure	8 bar
Inlet/outlet connection	Rp 1/2" / Rp 1/2"
Max. continuous flow	360 l/h
Height	600 mm
Width	380 mm
Weight	3.60 kg

Description

Fillsoft cartridge housing, compact basic fitting for treatment of filling and make-up water using an ion-exchanger process for the protection of heat generators and hot water heating systems according to VDI 2035.

Cartridge housing can be used in combination with the corresponding cartridge inserts (separate products) optionally for water softening or water demineralisation.

Empty housing is assembly-ready with wall mounting bracket for optional equipping with two each of i:

- Fillsoft water softening resin cartridge (green) FSP 6000 for the water softening
- Fillsoft Zero mixed bed resin cartridge (grey) FZP 3000 for water desalination

Fillsoft II individually comprising:

- two cylindrical propylene housings connected in series with brass thread connections for holding two each of the above mentioned water treatment cartridges and optional attachment of a Softmix mixing mechanism
- Flow limiter
- Shut-off ball valve with sampling tap

Components are arranged as a compact fitting for installation in the filling and makeup water line.