

Storatherm Heat H 800/R, Buffer cylinder for heating and cooling systems, grey, 3 bar



Thinking solutions.

Article number: 7784005



Features

Type	H 800/R
Colour	grey
Nominal capacity	780 l
Number of sleeves	9 St.
Operating temperature	95 °C
Max. perm. operating pressure	3 bar
Operating pressure	3 bar
Connection sleeve/flange	G 1 1/2"
Anschluss Flansch EFHR (berechnet)	DN110
EEHR sleeve connection	G 1 1/2"
Diameter without insulation	790 mm
Height	1825 mm
Depth	1025 mm
Tilt dimension approx.	1902 mm
Weight	121,00 kg

Description

Storatherm Heat

Buffer tank for storing heating and cooling water. Optionally available in upright versions with/without flange or with one/two internal heat exchangers for connection of external energy sources.

The connector series for heat sources and consumers are vertical, offset through 100° configured as charging or discharging connectors. Between these connector series there also vertically arranged screw-in options for sensor sleeves, thermometers or similar (3 x Rp 3/4, 1 x Rp 1/2). Tanks with bare-tube exchanges also have flow and return connectors to the tube bundle heating surface.

Storage tank of steel S235JR+AR, inside uncoated and outside corrosion protected.

The heat losses are measured on an externally certified test bed.