Variomat primary vessel VG 1500, for Variomat pressurisation stations, grey, 6 bar

Article number: 8600905

Thinking solutions.



Features

Type	VG 1500
Colour	grey
Nominal volume	1500 l
Max. useful volume	1350 l
Max. permissible system temperature	120 °C
Max. perm. safety temperature	110 °C
Min. perm. operating temperature	-10 °C
Max. perm. operating temperature	70 °C
Max. perm. operating pressure	6 bar
Connection	G1"
Diameter	1200 mm
Height	2127 mm
High water connection	460 mm
Tilt dimension approx.	2153 mm
Weight	300.00 kg

Description

Variomat VG
Diaphragm expansion vessel for Variomat one or two-pump controlled pressure maintenance stations, unpressurised, closed to atmosphere. Approval according to the EU Pressure Equipment Directive 2014/68/EU. The vessels are manufactured in accordance with DIN EN 13831, VDI 4708 and AD 2000.

- Floor-standing with foot structure
- Replaceable full diaphragm - compliant with DIN EN 13831
- Exterior plastic-coated
- With dipstick tube degassing
- including welded side socket for connection of a bladder rupture detector
- basic vessels VG incl. transducer for level sensing

Reflex Winkelmann GmbH • Gersteinstrasse 19 • 59227 Ahlen, Germany
+49 2382 7069-0 • www.reflex-winkelmann.com • info@reflex.de