

SINUS ProfiFixx MK50 P32 regulated flanged pump group DN50, for pump DN32, 220 mm, 3-way mixer 24V



Thinking solutions.

Article number: 4209339



Features

Type	MK50 P32
Pump group dimension	DN50
Pump dimension	DN32
Installed length installer supplied pump	220 mm
Type three-way mixer	ESBE VRG131 40-25 Rp 1 1/2"
Flow capacity of the three-way mixer	25.0
Actuator type	ESBE ARA659 3-point 24 V
Operating temperature	-10 °C - 110 °C
Operating pressure	0 bar - 6 bar
Weight	86.20 kg

Description

Flange pump group comprising pre-assembled and pre-insulated heating circuits compliant with the current building regulations (GEG) for direct installation without any on-site welding. Implemented with a regulated design with a three-way mixer. The entire ProfiFixx system is insulated in a visually uniform manner. The insulation is fitted using the supplied stainless-steel straps including quick-release connections and can be opened and closed again for maintenance purposes. The site provided pump is also freely accessible during operation, without it being necessary to remove the insulation.

The pump groups are provided with upper threaded flanges (female thread) for system-side connection. One 1/2" sensor sleeve each in flow and return. The insulation is not diffusion-tight.

The component is checked for 100% leak-tightness and primed in the factory.