

Storatherm Aqua Heat Pump AH 300/1_B, high efficiency tank with foil jacket, PUR foam, white, 10 bar



Article number: 7864000



Features

Type	AH 300/1_B
Colour	white
Insulation type	foil jacket, PUR foam
Insulation strength	51.5 mm
Energy efficiency class	B
Nominal capacity	279 l
Rated content corrugated pipe	23 l
Built acc. to	EN 12897
Operating temperature	95 °C
Perm. operating temperature heat exchanger	110 °C
Max. perm. operating pressure	10 bar
Perm. operating pressure heat exchanger	10 bar
Operating pressure	10 bar
Anschluss Flansch EFHR (berechnet)	DN110
EEHR sleeve connection	G 1 1/2"
Drinking water connection	R 1"
Connection heat surface(s)	G 1 1/4"
Circulation connection	G 3/4"
Connection cold/hot water	R 1"
Connection flow/return	G 1 1/4"
Conventional NL coefficient	13.3
Heat maintaining losses	70 W
Heating surface top	3.27 m ²
Diameter	700 mm
Diameter without insulation	598 mm
Height	1297 mm
Height without insul.	1266 mm
Depth	767 mm
Tilt dimension approx.	1455 mm
Weight	139.00 kg

Description

Storatherm Aqua Heat Pump

Hot water tank for indirect domestic hot water heating especially for heat pump applications in an upright version with one or two internal heat exchangers.

Storage tank of steel S235JR+AR, designed according to DIN EN 12897 and the Pressure Equipment Directive 2014/68/EU. Enamelling for hygienic perfect drinking water is performed according to DIN 4753 T3.

DHW tank up to 500 litre insulated with non-removable highly efficient insulation system according to DIN 4102-1 material class B2; DHW tank > 500 to 1000 litre insulated with 100mm; DHW tank > 1000 litre with 120mm removable fleece insulation, according to DIN 4102-1 material class B2.

Drinking water tank up to 500 litres available in energy efficiency classes B and C. DHW tank > 500 litres only available in energy efficiency class C.

The heat losses are measured on an externally certified test bed.