

Extwin TW 219.1 R, Micro-bubble / dirt separator with welded connector of painted steel, 110 °C, 10 bar

Article number: 8253260

reflex

Thinking solutions.



Features

Type	TW 219.1 R
Colour	grey
Housing material	painted steel
Installation variant	horizontal
Operating temperature	0 °C - 110 °C
Operating pressure	10 bar
Connection	219,1
Connection variant	welded connector
Max. volume flow	180,0 m³/h
Flow rate characteristic value kvs	780,6 m³/h
Diameter	409 mm
Height	1470 mm
Height mid-flange (air separation)	792 mm
Height mid-flange (dirt separation)	678 mm
Min. space requirement above	50 mm
Min. maintenance height	1000 mm
Installation length	650 mm
Weight	182,00 kg

Description

Extwin

Combined air / microbubble and sludge separator for heating and cold water systems or sealed liquid-filled system circuits.

Suitable for the media water and water / glycol mixtures up to a mixing ratio of 50 / 50%.

Fitting for collecting gas bubbles from the liquid flow via optimised separating element Flowpac or automatic, permanent discharge into the atmosphere via integrated, able to be isolated, Exvoid T large ventilator with 3-way valve bottom part.

Fitting for removing particles with a size from 5.0 micrometres from the flow of liquid by use of an insert designed specially for the purpose.

The cleaning and emptying of the dirt collection chamber is possible via a dedicated desludging ball valve without any necessity to interrupt operation.

Maintenance flange for easy housing access during cleaning and maintenance work.